

# Weatherproof Series

## Remote Emergency Lighting Fixtures



### WT Series

- PAR 36, surface-mounted industrial remote fixtures
- Available in single, double or triple head fixtures
- Durable thermoplastic construction suitable for industrial or high abuse areas
- Available in black (standard) and factory white
- Tool-less adjustment and aiming of lamp heads



### WSR Series

- Sealed beam, PAR 36, surface-mounted, rubber coated industrial remote fixture
- For use in high pressure hose down areas
- Available only in black



### PT Series

- NEMA-4X listed, surface-mounted, square industrial remote fixture
- Available with tungsten or quartz lamps in single or double head configurations
- Gray fiberglass base and clear polycarbonate lens



Project/Location:	Date:
Contractor:	Prepared by:

# Weatherproof Series

## WT Series

### Dimensions

WT1:	4.5" (11.4 cm) L x 7.25" (18.4 cm) H x 3.5" (8.9 cm) D
WT2:	4.5" (11.4 cm) L x 7.25" (18.4 cm) H x 11.75" (29.9 cm) D
Canopy:	4.19" (10.7 cm) Diameter



### Ordering Information

Series	# of Heads	Voltage/Wattage/Lamp Type	Colour	Options
WT= tungsten, par 36	1= single	-6/9= 6V - 9 watts, tungsten, wedge base	Blank= black	TC= teflon coated lens
WQ= halogen, par 36	2= double	-6/ __ = 6V - 18 or 25 watts, tungsten, D.C.B	WH= factory white	
	3= triple	-12/ __ = 12V - 9 or 18 watts, tungsten, wedge base		
		-12/25= 12V - 25 watts, tungsten, D.C.B.		
		-24/ __ = 24V - 9 or 18 watts, tungsten, wedge base		
		-24/25= 24V - 25 watts, tungsten, D.C.B.		
		-6 __ = 6V - 8, 12, or 20 watts, halogen, quartz bi-pin		
		-12/ __ = 12V - 8, 12, 20 or 55 watts, halogen, quartz bi-pin		
		-24/ __ = 24V - 20 or 70 watts, halogen, quartz bi-pin		
		-6/ __ = 6V - 9, 12, 18 or 25 watts, tungsten, sealed beam		
		-12/ __ = 12V - 12, 18 or 25 watts, tungsten, sealed beam		
		-6/ __ = 6V - 8, 12 or 20 watts, halogen, quartz sealed beam		
		-12/ __ = 12V - 8, 12 or 37 watts halogen, quartz sealed beam		
		-32/ __ = 32V - 18 or 25 watts, tungsten, D.C.B.		
		-120/ __ = 120V - 10, 15, 30 or 50 watts, tungsten, D.C.B.		
		*NOTE: " __ " = insert wattage required		

**EXAMPLE: WQ1-12/12**

## WSR Series

### Dimensions

WSR1:	4.5" (11.4 cm) L x 7.25" (18.4 cm) H x 3.5" (8.9 cm) D
WSR2:	4.5" (11.4 cm) L x 7.25" (18.4 cm) H x 11.75" (29.9 cm) D
Canopy:	4.19" (10.7 cm) Diameter



### Ordering Information


Series	Lamp Style	Lamp Type/Voltage/Wattage	Options
WSR= tungsten, par 36	1= single	-6/ __ = 6V - 9, 12, 18 or 25 watts, tungsten, sealed beam	TC= teflon coated lens
WHR= halogen, par 36	2= double	-12/ __ = 12V - 12, 18 or 25 watts, tungsten, sealed beam	
	3= triple	-6/ __ = 6V - 8, 12 or 20 watts, halogen, quartz sealed beam	
		-12/ __ = 12V - 8, 12 or 37 watts halogen, quartz sealed beam	

**EXAMPLE: WSR1-6/9TC**

## PT Series

### Dimensions

PT1	5.0" (12.7 cm) L x 5.0" (12.7 cm) H x 4.0" (10.2 cm) D
PT2	7.0" (17.8 cm) L x 5.0" (12.7 cm) H x 4.0" (10.2 cm) D



### Ordering Information

Series	# of Heads	Lamp Type/Voltage/Wattage	
PT= tungsten	1= single	-6/9= 6V - 9 watts, tungsten, wedge base	
PQ= halogen	2= double	-12/ __ = 12V - 9 or 18 watts, tungsten, wedge base	
		-24/ __ = 24V - 9 or 18 watts, tungsten, wedge base	
		-6V __ = 6V - 8, 12, or 20 watts, halogen, quartz bi-pin	
		-12/ __ = 12V - 8, 12, or 20 watts, halogen, quartz bi-pin	
		-24/20= 24V - 20 watts, halogen, quartz bi-pin	
		*NOTE: " __ " = insert wattage required	

**EXAMPLE: PQ1-12/12**

